Author Index

Ahlroos, T.	Type of motion and lubricant in wear simulation of polyethylene acetabular cup	301–310
Alam, S. K.	Elastography: ultrasonic estimation and imaging of the elastic properties of tissues	203–233
Alkalay, R. N.	The effects of design and configuration on the biomechanical response of an internal spinal fixator	137–146
Amstutz, H. C.	The role of acetabular component screw holes and/or screws in the development of pelvic osteolysis	147–153
Anderson, T.	Measurement of tissue motion	181–191
Ankersen, J.	Puncture resistance and tensile strength of skin simulants	493–501
Aspden, R. M.	Optimizing the configuration of cement keyholes for acetabular fixation in total hip replacement using Taguchi experimental design	485–492
Auger, D. D.	An axisymmetric contact model of ultra high molecular weight polyethylene cups against metallic femoral heads for artificial hip joint replacements	317–327
Bader, D. L.	The effects of design and configuration on the biomechanical response of an internal spinal fixator	137–146
Bamfaste, G.	Non-destructive and non-invasive observation of friction and wear of human joints and of fracture initiation by acoustic emission	41–48
Barbour, P. S. M.	A hip joint simulator study using simplified loading and motion cycles generating physiological wear paths and rates	455–467
Barker, T. M.	Discriminant analysis of human kinematic data: application to human lumbar spinal motion	447–453
Berstad, A.	Measurements of organ volume by ultrasonography	247–259
Besong, A. A.	The influence of lubricant on the morphology of ultra-high molecular weight polyethylene wear debris generated in laboratory tests	155–158
Birkbeck, A. E.	Puncture resistance and tensile strength of skin simulants	493–501
Birthistle, P.	An investigation of the performance of Biostop G and Hardinge bone plugs	361–365
Black, R. A.	Computer aided design and fabrication of models for *in vitro* studies of vascular fluid dynamics	1–4
Blunt, L.	Three-dimensional surface characterization for orthopaedic joint prostheses	49–68
Bourne, M.	Reconstruction of blood flow patterns in human arteries	411–421
Brands, P. J.	Non-invasive measurement of mechanical properties of arteries in health and disease	195–202
Brown, I. C.	The role of acetabular component screw holes and/or screws in the development of pelvic osteolysis	147–153
Burgess, I. C.	Evaluation of a hip joint simulator	469–473
Canestri, F.	On-line computer system to minimize laser injuries during surgery: preliminary system layout and proposal of the key features	69–76
Carlsson, L. V.	Press-fit acetabular cup fixation: principles and testing	33–39
Carpenter, T. K.	Local haemodynamics of arterial bypass graft anastomoses	401–409
Charnley, G. J.	Press-fit acetabular cup fixation: principles and testing	33–39
Chong, C. K.	Computer aided design and fabrication of models for *in vitro* studies of vascular fluid dynamics	1–4
Clark, C.	Comparison of flow in numerical and physical models of a ventricular assist device using low- and high-viscosity fluids	423–432
Collins, M. W.	Reconstruction of blood flow patterns in human arteries	411–421
Dearnley, P. A.	A review of metallic, ceramic and surface-treated metals used for bearing surfaces in human joint replacements	107–135
Deng, J.	Three-dimensional morphometry in ultrasound	235–245
Dominy, J.	Feasibility study on a composite material construction technique for highly stressed components in reciprocal walking orthoses for paraplegic patients	355–360
Dowson, D.	A multi-station hip joint simulator study of the performance of 22 mm diameter zirconia–ultra-high molecular weight polyethylene total replacement hip joints	77–90
Dowson, D.	Development of a ten-station, multi-axis hip joint simulator	311–316
Edwards, D. H.	Integration of non-linear cellular mechanisms regulating microvascular perfusion	369–383
Engh, C. A.	The role of acetabular component screw holes and/or screws in the development of pelvic osteolysis	147–153

© IMechE 1999

Fish, P. J.	Ultrasonic investigation of blood flow	169–180
Fisher, J.	The influence of lubricant on the morphology of ultra-high molecular weight polyethylene wear debris generated in laboratory tests	155–158
Fisher, J.	The influence of continuous sliding and subsequent surface wear on the friction of articular cartilage	329–345
Fisher, J.	A hip joint simulator study using simplified loading and motion cycles generating physiological wear paths and rates	455–467
Fisher, J.	Analysis of debris from brushing the femoral canal with a plastic brush—a potential cause of loosening in total hip replacement	503–506
Forster, H.	The influence of continuous sliding and subsequent surface wear on the friction of articular cartilage	329–345
Franke, R.-P.	Non-destructive and non-invasive observation of friction and wear of human joints and of fracture initiation by acoustic emission	41–48
Garra, B.	Elastography: ultrasonic estimation and imaging of the elastic properties of tissues	203–233
Germain, M. A.	Analysis of debris from brushing the femoral canal with a plastic brush—a potential cause of loosening in total hip replacement	503–506
Gilja, O. H.	Measurements of organ volume by ultrasonography	247–259
Girish Kumar, N. V.	An investigation of the performance of Biostop G and Hardinge bone plugs	361–365
Goldsmith, A. A. J.	A multi-station hip joint simulator study of the performance of 22 mm diameter zirconia–ultra-high molecular weight polyethylene total replacement hip joints	77–90
Goldsmith, A. A. J.	Development of a ten-station, multi-axis hip joint simulator	311–316
Griffith, T. M.	Integration of non-linear cellular mechanisms regulating microvascular perfusion	369–383
Griffith, T. M.	Reconstruction of blood flow patterns in human arteries	411–421
Harris, P. L.	Local haemodynamics of arterial bypass graft anastomoses	401–409
Harris, W. H.	The role of acetabular component screw holes and/or screws in the development of pelvic osteolysis	147–153
Hausken, T.	Measurements of organ volume by ultrasonography	247–259
Heng, S. M.	An axisymmetric contact model of ultra high molecular weight polyethylene cups against metallic femoral heads for artificial hip joint replacements	317–327
Hoeks, A. P. G.	Non-invasive measurement of mechanical properties of arteries in health and disease	195–202
Holstein, H.	The effect of cartilage deformation on the laxity of the knee joint	19–32
Hoskins, P. R.	A review of the measurement of blood velocity and related quantities using Doppler ultrasound	391–400
How, T. V.	Computer aided design and fabrication of models for *in vitro* studies of vascular fluid dynamics	1–4
How, T. V.	Local haemodynamics of arterial bypass graft anastomoses	401–409
Huss, R. A.	The effect of cartilage deformation on the laxity of the knee joint	19–32
Hutchison, J. D.	Optimizing the configuration of cement keyholes for acetabular fixation in total hip replacement using Taguchi experimental design	485–492
Ingham, E.	The influence of lubricant on the morphology of ultra-high molecular weight polyethylene wear debris generated in laboratory tests	155–158
Ingham, E.	Analysis of debris from brushing the femoral canal with a plastic brush—a potential cause of loosening in total hip replacement	503–506
Ishihara, K.	Effect of phospholipidic boundary lubrication in rigid and compliant hemiarthroplasty models	5–18
Jacobsson, C. M.	Press-fit acetabular cup fixation: principles and testing	33–39
Jansson, T.	Estimation of blood perfusion using ultrasound	91–106, 193
Jiang, X. Q.	Three-dimensional surface characterization for orthopaedic joint prostheses	49–68
Jin, Z. M.	An axisymmetric contact model of ultra high molecular weight polyethylene cups against metallic femoral heads for artificial hip joint replacements	317–327
Kallel, F.	Elastography: ultrasonic estimation and imaging of the elastic properties of tissues	203–233
König, C. S.	Comparison of flow in numerical and physical models of a ventricular assist device using low- and high-viscosity fluids	423–432
Konofagou, E.	Elastography: ultrasonic estimation and imaging of the elastic properties of tissues	203–233
Krouskop, T.	Elastography: ultrasonic estimation and imaging of the elastic properties of tissues	203–233
LaBerge, M.	Effect of phospholipidic boundary lubrication in rigid and compliant hemiarthroplasty models	5–18
Langton, C. M.	Acoustic and ultrasonic tissue characterization—assessment of osteoporosis	261–269
Lindström, K.	Estimation of blood perfusion using ultrasound	91–106, 193
Linney, A. D.	Three-dimensional morphometry in ultrasound	235–245
Long, Q.	Reconstruction of blood flow patterns in human arteries	411–421

© IMechE 1999

McCleod, N.	Feasibility study on a composite material construction technique for highly stressed components in reciprocal walking orthoses for paraplegic patients	355–360
McCombe, P.	Discriminant analysis of human kinematic data: application to human lumbar spinal motion	447–453
McCormack, B. A. O.	Quantification of interdigitation at bone cement/cancellous bone interfaces in cemented femoral reconstructions	347–354
McDicken, W. N.	Measurement of tissue motion	181–191
Macdonald, W.	Press-fit acetabular cup fixation: principles and testing	33–39
Magnusson, M. L.	A review of studies on seated whole body vibration and low back pain	435–446
Maher, S. A.	Quantification of interdigitation at bone cement/cancellous bone interfaces in cemented femoral reconstructions	347–354
Major, R. E.	Feasibility study on a composite material construction technique for highly stressed components in reciprocal walking orthoses for paraplegic patients	355–360
Makarem, R.	Analysis of debris from brushing the femoral canal with a plastic brush—a potential cause of loosening in total hip replacement	503–506
Mathews, B. J.	The influence of lubricant on the morphology of ultra-high molecular weight polyethylene wear debris generated in laboratory tests	155–158
Mburu, G.	Optimizing the configuration of cement keyholes for acetabular fixation in total hip replacement using Taguchi experimental design	485–492
Mokhtarzedeh-Dehghan, M. R.	Comparison of flow in numerical and physical models of a ventricular assist device using low- and high-viscosity fluids	423–432
Nakabayashi, N.	Effect of phospholipidic boundary lubrication in rigid and compliant hemiarthroplasty models	5–18
Ng, H. W.	An axisymmetric contact model of ultra high molecular weight polyethylene cups against metallic femoral heads for artificial hip joint replacements	317–327
Njeh, C. F.	Acoustic and ultrasonic tissue characterization—assessment of osteoporosis	261–269
Nokes, L. D. M.	The use of low-frequency vibration measurement in orthopaedics	271–290
O'Connor, J. J.	The effect of cartilage deformation on the laxity of the knee joint	19–32
Ødegaard, S.	Measurements of organ volume by ultrasonography	247–259
Ophir, J.	Elastography: ultrasonic estimation and imaging of the elastic properties of tissues	203–233
Persson, H. W.	Estimation of blood perfusion using ultrasound	91–106, 193
Pope, M. H.	A review of studies on seated whole body vibration and low back pain	435–446
Powell, G. L.	Effect of phospholipidic boundary lubrication in rigid and compliant hemiarthroplasty models	5–18
Prendergast, P. J.	An investigation of the performance of Biostop G and Hardinge bone plugs	361–365
Rattray, A.	Computer aided design and fabrication of models for *in vitro* studies of vascular fluid dynamics	1–4
Reneman, R. S.	Non-invasive measurement of mechanical properties of arteries in health and disease	195–202
Rogers Foy, J.	Effect of phospholipidic boundary lubrication in rigid and compliant hemiarthroplasty models	5–18
Rowe, C. S.	Computer aided design and fabrication of models for *in vitro* studies of vascular fluid dynamics	1–4
Rowe, C. S.	Local haemodynamics of arterial bypass graft anastomoses	401–409
Saikko, V.	Type of motion and lubricant in wear simulation of polyethylene acetabular cup	301–310
Schmalzried, T. P.	The role of acetabular component screw holes and/or screws in the development of pelvic osteolysis	147–153
Schwalbe, H.-J.	Non-destructive and non-invasive observation of friction and wear of human joints and of fracture initiation by acoustic emission	41–48
Seedhom, B. B.	Cross-sectional geometry of the human femur in the mid-third region	159–166
Sharpe, D.	The effects of design and configuration on the biomechanical response of an internal spinal fixator	137–146
Shortland, A. P.	Computer aided design and fabrication of models for *in vitro* studies of vascular fluid dynamics	1–4
Sivanesan, S.	Computer aided design and fabrication of models for *in vitro* studies of vascular fluid dynamics	1–4
Smith, S. L.	Evaluation of a hip joint simulator	469–473
Smith, S. L.	A comparison between gravimetric and volumetric techniques of wear measurement of UHMWPE acetabular cups against zirconia and cobalt–chromium–molybdenum femoral heads in a hip simulator	475–483
Stallard, J.	Feasibility study on a composite material construction technique for highly stressed components in reciprocal walking orthoses for paraplegic patients	355–360

© IMechE 1999

Stanton, A. V.	Haemodynamics, wall mechanics and atheroma: a clinician's perspective	385–390
Stephenson, P.	Cross-sectional geometry of the human femur in the mid-third region	159–166
Stone, M. H.	The influence of lubricant on the morphology of ultra-high molecular weight polyethylene wear debris generated in laboratory tests	155–158
Stone, M. H.	A hip joint simulator study using simplified loading and motion cycles generating physiological wear paths and rates	455–467
Stout, K. J.	Three-dimensional surface characterization for orthopaedic joint prostheses	49–68
Thomson, K. D.	Estimation of loads in the lumbar spine during slow symmetrical lifts and a method for their reduction	293–299
Thomson, R. D.	Puncture resistance and tensile strength of skin simulants	493–501
Tipper, J. L.	The influence of lubricant on the morphology of ultra-high molecular weight polyethylene wear debris generated in laboratory tests	155–158
Tipper, J. L.	Analysis of debris from brushing the femoral canal with a plastic brush—a potential cause of loosening in total hip replacement	503–506
Unsworth, A.	Evaluation of a hip joint simulator	469–473
Unsworth, A.	A comparison between gravimetric and volumetric techniques of wear measurement of UHMWPE acetabular cups against zirconia and cobalt–chromium–molybdenum femoral heads in a hip simulator	475–483
Vanezis, P.	Puncture resistance and tensile strength of skin simulants	493–501
Varghese, T.	Elastography: ultrasonic estimation and imaging of the elastic properties of tissues	203–233
Waide, D. V.	An investigation of the performance of Biostop G and Hardinge bone plugs	361–365
Wilder, D. G.	A review of studies on seated whole body vibration and low back pain	435–446
Williams III, P. F.	Effect of phospholipidic boundary lubrication in rigid and compliant hemiarthroplasty models	5–18
Willigers, J. M.	Non-invasive measurement of mechanical properties of arteries in health and disease	195–202
Woollam, P. J.	Feasibility study on a composite material construction technique for highly stressed components in reciprocal walking orthoses for paraplegic patients	355–360
Wroblewski, B. M.	Analysis of debris from brushing the femoral canal with a plastic brush—a potential cause of loosening in total hip replacement	503–506
Xu, X. Y.	Reconstruction of blood flow patterns in human arteries	411–421

© IMechE 1999